

#### US006153075A

# United States Patent [19]

## Nemelka

## [11] Patent Number:

6,153,075

[45] **Date of Patent:** 

Nov. 28, 2000

METHODS USING
ELECTROPHORETICALLY DEPOSITED
PATTERNABLE MATERIAL

[75] Inventor: Jefferson O. Nemelka, Boise, Id.

[73] Assignee: Micron Technology, Inc., Boise, Id.

[21] Appl. No.: 09/031,955

[22] Filed: Feb. 26, 1998

## [56] References Cited

#### U.S. PATENT DOCUMENTS

3,387,975	6/1968	Tamura 96/36.1
4,592,816	6/1986	Emmons et al 204/180.6
4,751,172	6/1988	Rodriguez et al 430/314
4,891,110	1/1990	Libman et al 204/181.1
5,004,672	4/1991	D'Ottavio et al 430/314
5,196,098	3/1993	Rodriguez et al 204/180.2
5,205,770	4/1993	Lowrey et al 445/24
5,232,549	8/1993	Cathey et al 456/633
5,459,480	10/1995	Browning et al 345/75
5,466,358	11/1995	Kiyomiya et al 204/490
5,486,126	1/1996	Cathey et al 445/25
5,503,582	4/1996	Cathey, Jr. et al 445/24
5,588,359	12/1996	Hofmann et al 101/128.21
5,601,751	2/1997	Watkins et al 252/301.4 R
5,607,818	3/1997	Akram et al 430/311
5,634,858	6/1997	Stansbury
5,662,831	9/1997	Chadha 252/301.4 R
5,667,418	9/1997	Fahlen et al 445/25
5,675,212	10/1997	Schmid et al 313/422
5,931,713	8/1999	Watkins et al 495/55

### OTHER PUBLICATIONS

Eagle®2005 Developer, Product pamphlet, Shipley Company, Inc. (1991).

Eagle®2007 Remover, Product pamphlet, Shipley Company, Inc. (1992).

Eagle®2100 ED Photo Resist, Product pamphlet, Shipley Company, Inc. (1992).

Jacob, T., et al., "Liquid Resist Allows land Size Reduction," *Electronic Packaging & Production*, 36, 27–34 (1996).

Miller, P., "Inner-Layer Imaging using a Novel Electrophoretic Resist," Nepcon East 1989 Conference, Boston, MA (1989).

Murray, J., "Ed Processes Revisted," PC FAB, 22-23 (1992).

Shmulovich, J., et al., "Successful Development of Non–Planar Lithography for Micro–Machining Applications," *Integrated Photonics Research*, 6, 354–357 (1996).

Vidusek, D., "Electrophoretic Photoresist Technology: An Image of the Future—Today," *Circuit World*, 15, 6–10 (1989).

Primary Examiner—Kishor Mayekar Attorney, Agent, or Firm—Mueting, Raasch & Gebhardt, P.A.

## [57] ABSTRACT

Methods for use in the production of a display include providing a substrate assembly of a face plate of the display including a conductive surface at a first side thereof. One or more projections extend from the first side of substrate assembly. A patternable material, e.g., electrophoretically depositable resist, is electrophoretically deposited on at least the conductive surface and adjacent the projections, e.g., spacers such as nonconductive spacers or spacers that have at least portions thereof that are slightly conductive. The method may further include patterning the patternable material for use in deposition of light emitting elements on the conductive surface. Light emitting elements of one or more colors may be formed. In addition, the substrate assembly including the conductive surface may have one or more nonconductive regions formed on the conductive surface; the one or more nonconductive regions having a predetermined thickness. A layer of patternable material is formed by electrophoresis over the conductive surface and over the one or more nonconductive regions. Such patternable material may then be patterned and used in formation of light emitting elements. Further, structures used in the production of a face plate of a display are also provided.

### 21 Claims, 12 Drawing Sheets

